

Opus glass.

 www.opusglass.co.za

 010 132 9022


 info@opusglass.co.za


 26 Tuinfluiter Cres,
Rabie Ridge, Midrand, 1688



Clearview Frameless Folding Door

*Are you looking to enclose your patio or balcony and still keep it open and bare?
As ironic as this might seem, the Clearview Frameless Folding Door System
offers a splendid option.*

 This flexible system constitutes of several interconnected panels of toughened safety glass; and when neatly folded and packed to one side of the structure creates an open plan between the interior and outdoors, and bargains the much desired cooling fresh air breezes on hot summer days.

 In contrast, this system is also designed and tested to withstand very high winds and rain. Owing to its minimal use of aluminium and steel design, this exquisite and lush system will accordingly not compromise the stunning outdoor views on your property.



Please note the design specifications of this system below:

Property	Specification/Dimension
Powder coating option	Bronze/White
Thickness of toughened safety glass (TSG)	8mm/ 10mm
Maximum width/ panel	700mm
Maximum height/ panel	3300mm
Handle design	Standard knob/ Pull Handle (Custom)



What determines glass thickness and other properties?

For panels with a height of 2.4m or less, 8mm toughened safety glass (TSG) is used. Panels with a height higher than 2.4m are glazed with 10mm TSG.

For panels with a height of 2.4m or less, two rows of hinges are used. Above this height, a third row of hinges is added.

Only an odd number of panels may be stacked to one side, with a maximum of 7 panels. A top roller and a bottom guide are installed on every second panel.

For an even number of panels, a hinged receiving panel may be installed on frame opposite the stacking end.



Various tinted glass options are available.



Proudly AAAMSA compliant